

STANDARD FEATURES	LCROHD -500	LCROHD-900
PTRO21-2540 Membrane 600 GPD @150 PSI (500 PPM)	~	
PTRO21-4021 Membrane 900 GPD@150 PSI (1,500 PPM)		~
Automatic Shut-off Valve (when tank is full)	~	~
High Flow Brass Rotary Vane Pump	 ✓ 	~
Powder Coated, Heavy Duty Steel Frame	~	~
Built-in Pressure Gauge 0-160 PSI, Glycerine Filled	~	~
Complete Installation Kit and Instruction Manual	 ✓ 	~
20" Pre Filter Cartridges inside 20" Filter Housings	~	~
Made with High Quality, Certified and Listed Components	~	~
1-year Limited Warranty	· ·	~
Automatic Low Pressure Switch	~	~
Stainless Needle Valve Adjusts Concentrate to Permeate Ratio	 ✓ 	~
Gallons Per Hour	20 GPH	37 GPH



OPTIONS FOR LCRO-HD Consult our sales department for more information

- 1. Install High Pressure Switch (for pressure bladder tanks)
- 2. Install Normally Closed Float Switch (for atmospheric Storage tanks)
- 3. Add Atmospheric Storage Tank
- 4. Add Pressure Bladder Tank
- 5. Install TDS Monitor

MODEL	PRODUCTION		ELECTRICAL	PRODUCT RECOVERY	TDS REJECTION	SHIPPING WEIGHT	SHIPPING DIMENSIONS
	GPD	LPH	110V-60HZ			System	System
LCROHD-600	600	94	OR	Adjustable	99%	69 LBS	21X1 <mark>3X38</mark>
LCROHD-900	900	141	220V-50HZ	Adjustable		72 LBS	21X13X38

DISTRIBUTED BY

